



Acoustical Flat Wall Panel (WP) combines fabric and sound absorbing fiberglass acoustic panels to create a dynamic sound product that enhances the beauty of your walls. Walls and ceilings are now able to provide better sound reflection and look good too!

Standard size for AWP-1 or AWP-2 panels is 4' x 8'. Custom sizes or smaller panels require drawing specifications to ensure accuracy.

## CORE

6-7 pcf fiberglass  
1" or 2" thickness

## SIZES

4' x 8' standard  
Custom sizes as requested

## MOUNTING

Back mounted with screw-in clips secured to substrate with Rotofast Anchors, "Z" Clips, Impaling Clips or Adhesive based on specifications.

## FINISH

Standard fabric:  
Guilford of Maine, Anchorage 2335  
Other panel fabrics approved upon submittal

## EDGES

Square  
Hardened  
Beveled

## FIRE RATING

ASTM E84 Class "A" materials

## SOUND ABSORPTION

Hz	125	250	500	1000	2000	4000	N.R.C.
WP-1"	.10	.25	.84	1.08	1.13	1.11	.85
WP-2"	.42	.89	1.12	1.07	1.10	1.09	1.05

## FABRIC

Standard fabric is Guilford of Maine, Anchorage 2335. Other *panel* fabrics may require submittal prior to approval.

## PANELS

Please visit our website at [www.dimensionlacoustics.com](http://www.dimensionlacoustics.com) for all current available information.

# Beautiful Sound Control

○888-287-4183 ○303-774-9992 ○fax 303-774-0081  
[www.dimensionlacoustics.com](http://www.dimensionlacoustics.com)